

## Elevance Clean™ 1200 Spray & Rinse - Formula 1201

### Introduction

The following Elevance Clean™ 1200 starting point formulation removes greasy, particulate soils commonly encountered in transportation maintenance, repair and operations (MRO), including bitumen, asphalt, oils, complex greases and petroleum. This prototype formulation is designed for powerful degreasing in the most challenging scenarios.

Ingredients	% by Weight	Functionality	Supplier
<i>Elevance Clean™ 1200</i>	<i>80</i>	<i>Solvent</i>	<i>Elevance</i>
BIO-SOFT® N91- 2.5	10	Emulsifier	Stepan
Diethylene glycol butyl ether	10	Rinse Aid	Various

### Procedure

Load Elevance Clean™ 1200, BIO-SOFT® N91-2.5 and diethylene glycol butyl ether into a mixing vessel and stir until homogeneous.

### Instructions for Use

Apply to soiled surface and allow to dwell for some time. Pressure rinse with water to remove dissolved, softened and loosened soil.

### Notes

In United States, Elevance Clean™ 1200 is a low vapor pressure VOC (LVP-VOC), therefore its contribution to the VOC calculation is zero. Elevance Clean™ 1200 does not contribute to the VOC calculation because of its high boiling point and low vapor pressure.

Please refer to the Safety Data Sheet for regulatory information for the respective formulation ingredients described in these starting point formulations. It is the responsibility of the end user to review the chemical control regulations.

Elevance Renewable Sciences hopes that this suggested formulation are helpful to our customers. It is noted that this is only a representative formulation and not a commercialized product. Before any formulation is commercialized, it should be thoroughly tested to determine its performance and safety. It is our customer's responsibility to obtain any necessary government clearance, license or registration.